

Magnetic Sign Care & Handling

Thank you for your purchase from Checkers Custom Signs. Please review the following instructions prior to installing your magnetic signs.

Should you have any questions or concerns about the proper use of this product, please contact us.

These instructions are available for download from our website
www.CheckersCustom.com/resources.html



www.CheckersCustom.com
717-526-0489

Storing Flexible Magnet

- When not using flexible magnetic sheet, keep it in a clean, dry place.
- Store rolled stock on end to keep it from developing flat spots.
- Store rolled sign material on end with the printed or vinyl side out
- Stack flat magnet on a level surface. Avoid placing objects (such as cartons) on top that could damage the face; do not stack with magnetic sides facing each other.

Preparing Magnetic-Receptive Surfaces

- Before affixing magnetic sheet to a metal surface, be sure all surface paints, clear coats and waxes are cured (hardened).*
- Clean the metallic surface and the magnet with mild detergent. *Wipe with a soft cloth or allow to dry.

*(Approximate curing times: paint—90 days; clear coat—60 days; wax—2 days.)

Applying Flexible Magnet

- Before applying, test all inks and paints used on the magnet for adhesion and solvent compatibility.
- If possible, affix to smooth, flat or gently curved metallic surfaces.
- Make sure the entire magnet is flat against the metal surface (i.e., no air pockets).
- If you place the magnet in the wrong position, completely remove the magnet from the surface and reaffix. Do not pull the magnet across the surface, or it may stretch due to the resistance caused by the high magnetic strength.
- Avoid use on horizontal metal surfaces exposed to direct sunlight (such as automobile hoods), temperatures exceeding 160°F (71°C) or temperatures below -15°F (-26°C). Exposure to cold weather will make the magnet more brittle so use caution when handling.
- Be aware that long-term use on surfaces frequently exposed to sunlight (such as vehicles) can result in uneven fading of the surface because the magnet-covered area is shielded from ultraviolet rays.
- Avoid use on non-metallic body fillers, simulated wood grain siding and repainted surfaces.

Cleaning Flexible Magnet

- To guard against moisture and dirt buildup between the magnet and the metal surface (particularly on outdoor applications), remove the magnet at regular intervals. Clean both the magnet and metal surface with mild detergent; wipe with a soft cloth or allow to air-dry. (For vehicle-mounted signs, remove and clean DAILY.)
- After waxing and polishing, allow 2 days for wax to cure before applying magnets.

Checkers Custom Signs Uses:



"The Force in Flexible Magnetics", "Magnum", "Magnum Magnetics" and the "M" and arrow symbol, individually and in combination, are U.S. registered trademarks of Magnum Magnetics Corporation.

The item(s) noted here is/are provided "as is". Checkers Custom Signs does not warrant the product or installation, including warranties of merchantability or fitness for a particular purpose.

Buyer is solely responsible for proper use and installation of this product.

© Copyright 2006 Checkers Custom Signs - All Rights Reserved

1104 Brittany Boulevard, Harrisburg, Pennsylvania 17109-1207